

# M-8025NB S3 SRC/HRO

## Slip-On Dealer Work Boots (Metal Free)

Superior Chelsea Design Ankle Work Boots is made with Full Grain Cow Leather and PU/Rubber Outsole. It is designed as EN ISO 20345:2011 Quality with S3 category.



Upper : Full Grain Cow Leather (TPU Overcap)

Lining : Breathable Sandwich Air Mesh

Insole : Comfortable EVA Coated Mesh

Outsole : PU/Rubber Injection (HRO 300°)

Toecap : Composite Toecap

Penetration : Kevlar Midsole Plate

Size : EU 37-47#, UK 3-13#, US4-14#

CE EN ISO 20345:2011 S3 SRC

Application : Construction, Logistics, Mechanics, Glasses Installation, Workshop, Oil & Gas, Chemical Factory etc



200 JOULE  
TOECAP



SLIP-  
RESISTANT



SHOCK  
ABSORPTION



ANTI-STATIC



ANTI-NAIL  
MIDSOLE



PETROL AND  
CHEMICAL  
RESISTANT



WATER  
RESISTANT



OIL  
RESISTANT




ELECTRO-STATIC  
DISCHARGE



### Composite Toe Cap Protection • AN1-EN12568

It is made with light weight fiber-glass material, which can reach 200 joules from falling or rolling objects. It is stronger and more light than steel toecap.



### Kevlar Plate Protection • AN1-EN12568

Kevlar midsole plate, is zero-penetration resistant. It can resist 1100 newtons nail puncture from sharp objects. It is stronger and more flexible than steel plate.



### Water Resistant Cow Leather Upper • CE EN ISO 20345:2011

High quality full grain cow leather with thickness 1.6-1.8mm. It is treated with water resistant coating to protect feet from raining workday. Tear strength is required 10% higher than Europe test requirement, to reach longer lifespan.



### Heavy Duty PU/Rubber Outsole • CE EN ISO 20345:2011

The outsole is made with PU/Rubber material. The midsole is 45±5 degree hardness PU, which is soft and shock absorption. The outsole is natural rubber with 5%-10% nitrile, which can pass 300 °C heat resistant HRO test.

## Sole Bonding Strength Test

- EN ISO 20344:2011, 5.2 (Between Upper & Sole)
- Average Test Result 5.8±5 (N/mm)



### Upper, Lining & Bonding Strength Test Result

Leather Tear Strength ≥	120.0 Newtons
Leather Tensile Properties ≥	15.0 N/mm <sup>2</sup>
Lining Tear Strength ≥	15.0 N/mm
Bonding Strength ≥	4.0 N/mm

✓ Protection With Slip Resistant (SRC)	Result
Test Requirement : SRA (Eurotile 2+Nal S) Forward Heel Slip ≥0.28 & Forward Flat Slip: ≥0.32 SRB (Steel Floor+Glycerine) Forward Heel Slip ≥0.13 & Forward Flat Slip: ≥0.18	PASS
Standards : EN ISO20344:2011(5.11) , SRC Means both SRA & SRB requirements are fulfilled.	
✓ Protection Against Heat Risk 300°C	Result
Test Requirement : The Outsole Did Not Melt & Did Not Develop Any Cracks When Bent Aound Mandrel	PASS
Standards : EN ISO 20344:2011(8.7). 300°C HRO=Heat Resistant	
✓ Protection Resistant to Fuel Oil	Result
Test Requirement : Change in Volume and Change in Hardness (Outsole) is No More Than +12%(*)	PASS
Standards : EN ISO 20344:2011(8.6.1)	
SAFETOE Standard Package Instruction (Average 42# for Reference)	
Shoes Weight : 1.2-1.3 KGS /Pair	Carton Weight : 13-14 KGS /Carton
1 Pair / Color Box , Dimensions : 32×23×12CM	10 Pair / Carton , Dimensions : 62×47×33CM



### User Instructions:

- 1.) RECOMMENDED TO USE : Construction, Logistics, Mechanics, Glasses Installation, Workshop, Farming, Garden, Oil & Gas, Chemical Factory etc.
- 2.) LIMITATION TO USE: It is very important that footwear selected must be suitable for the right workplaces. The protection against risks or hazards which are not mentioned in this document is not warranted.
- 3.) FITTING & SIZE: All footwear are marked with standard size on tongue label. Some are with different size comparison, such as EU size, UK size, US size etc. Please wear footwear in a suitable size.

- 4.) STORAGE: Keep the footwear in its original packaging, under ordinary temperature, non-humidity conditions and in clean, covered and ventilated premises.
- 5.) CLEANING: Clean footwear regularly by high quality cleaning treatments recommended as suitable for the purpose. Don't use caustic or corrosive cleaning agents.